



Flexible Expansion

Up to 50 units in parallel, 5.12kWh--256kWh capacity



IP66 Protection

Fearless of outdoor insatallition, strong environmental adaptability



Ultra Safe

Intelligent fire extinguishing system, detects and extinguishes fire in 5s



Automatic Self-heating

-20°C to 55°C operating temperature (optional)



Easy Installation

Support wall-mounted, floor-mounted installations, high space utilization

Model	PowerHaus
Battery Type	LiFePO₄
Nominal Voltage/Capacity	51.2V/100Ah
Nominal Battery Energy	5.12kWh
Operating Voltage	44.8V-57.6V
Recomended Charge & Discharge C Rate	0.5C
Recommended Charge/Discharge Current	50A
Max. Charge/Discharge Current	Charge:75A/Discharge:100A
Peak Discharge Current	200A@2min
Cycle Life*	≥8000 cycles/10 years
Depth of Discharge (DOD)	95%
Charge Temperature	0°C~55°C/-20°C~55°C (optional)
Discharge Temperature	-20 ℃~55℃
Protection Level	IP66
Dimension[W/D/H]	450/165/640 mm
Net Weight	54.4kg
Maximum Parallel Modules	50
Fire Protection System	Built-in aerosol fire extinguisher
WIFI Module	Built-in WiFi module,APP OTA
Communication	CAN/RS485
Certification	UN38.3/IEC62619/CE-EMC
Compatible Inverters	Solis、GOODWE、Growatt、SMA、Victron、DEYE、APsystem etc.

 $^{^{\}ast}$ Test conditions: 0.2C Charging & Discharging. @25°C, 95% DOD

