

DH200Y

DH200Y is the first high-security, high-energy density, DC1000V liquid-cooled all-in-one energy storage system designed for grid-connected projects. Single cabinet capacity of 232kWh, maximum support for 10 machines in parallel, expandable to 2.3MWh. With a 9% increase in energy density and a 10% reduction in floor space.



Flexible Expansion

Maximum support for 10 machines in AC parallel, expandable to 2.3MWh; reserved DC expansion interface.



Economical

Occupies an area of 1.58m², energy density up to 147kWh/m², low installation costs



Ultra Safe

Triple-level fire suppression + active exhaust + passive explosion-proof design to eliminate hidden hazards and ensure safe operation.



Smart Temperature Control

PACK smart liquid cooling+PCS smart air cooling, cluster-level temperature difference ≤ 3°C



High Level Protection

PACK+PCS IP65,C3/C5 anti-corrosion grade optional, handles harsh environments



Simple O&M

Modular design, pre-maintenance solution for easy access and O&M, and support for online monitoring and O&M

SPECIFICATION

| Model | DH200Y |
|------------------------------------|--|
| Battery | |
| Battery Type | LiFePO ₄ |
| Battery Capacity | 280Ah |
| PACK Configuration | 1P52S*5 |
| Rated Current | 140A |
| Max. Current | 160A |
| Voltage Range | 754~936Vdc |
| Nominal Capacity | 232kWh |
| On-grid AC Side | |
| Rated Power | 100kW |
| AC Maximum Current | 145A |
| AC Rated Voltage | 400Vac |
| Wiring Method | 3P4L+PE |
| Frequency | 50Hz |
| Power Factor | 1(Leading)~1(Lagging) |
| THDi | ≤3% (Rated power) |
| Max. Number Of Parallel Expansions | 10 |
| System | |
| Weight | 2600±100kg |
| Dimension (W*D*H) | 1055*1475*2400mm |
| Max. Efficiency | 90% |
| Liquid-cooling Power | 2.5kW (Cooling), 2kW (Heating) |
| Operating Temperature | -20~50°C (Derating above 45 °C) |
| Operating Humidity | 0~95%RH (Non-condensing) |
| Ingress Protection | IP55 |
| Anti-corrosion Grade | C3(Optional C5) |
| Cooling Method | PACK Liquid-cooling + PCS Air-cooling |
| Noise | ≤75dB |
| Elevation | 3000m (Derating above 2000m) |
| Display | Touch screen |
| Fire Protection | Aerosol, Multi-sensor/Water ingress, Explosion-proof ventilation |
| Communication | Ethernet/4G/RS485 |
| Certification | CQC, CE, TUV, LVD, UN38.3 |

